message.

only correct response to an uplink free text

CPDLC Message Sets			Operational Definition in PANS-ATM (Doc 4444)			
FANS 1/A	ATN B1	Response	Message Element Identifier	Message Element Intended Use	Format for Message Element Display	
DM0 WILCO	DM0 WILCO	N	RSPD-1	Indication that the instruction is under- stood and will be complied with.	WILCO	
DM1 UNABLE	DM1 UNABLE	N	RSPD-2	Indication that the message cannot be complied with.	UNABLE	
DM2 STANDBY	DM2 STANDBY	N	RSPD-3	Indication that the message will be re- sponded to shortly.	STANDBY	
DM3 ROGER Note – ROGER is the	DM3 ROGER	N	RSPD-4	Indication that the message is re-	ROGER	

ceived.

TBL 5-3-13 Standard Response Downlink Message Elements (RSPD)

TBL 5-3-14 Supplemental Uplink Message Elements (SUPU)

CPDLC Message Sets			Operational Definition in PANS-ATM (Doc 4444)		
FANS 1/A	ATN B1	Response	Message Element Identifier	Message Element Intended Use	Format for Message Element Display
UM166 DUE TO TRAFFIC	N/A	N	SUPU-2	Indication that the associated message	DUE TO (specified reason
UM167 DUE TO AIRSPACE RE- STRICTION				is issued due to the specified reason.	uplink)

TBL 5-3-15
Supplemental Downlink Message Elements (SUPD)

CPDLC Message Sets			Operational Definition in PANS-ATM (Doc 4444)		
FANS 1/A	ATN B1	Response	Message Element Identifier	Message Element Intended Use	Format for Message Element Display
DM65 DUE TO WEATHER	DM65 DUE TO WEATHER	N	SUPD-1	Indication that the associated message is issued due to the specified reason.	DUE TO (specified reason downlink)
DM66 DUE TO AIR- CRAFT PERFOR- MANCE	DM66 DUE TO AIRCRAFT PER- FORMANCE				