

Table B1A – Minimum FTD Requirements						
QPS REQUIREMENTS			INFORMATION			
Entry Number	General FTD Requirements	FTD Level				Notes
		4	5	6	7	
	(5) Overlay or masking, including bezels and bugs, as applicable, replicates the airplane panel(s); (6) Instrument controls and switches replicate and operate with the same technique, effort, travel and in the same direction as those in the airplane; (7) Instrument lighting replicates that of the airplane and is operated from the FSTD control for that lighting and, if applicable, is at a level commensurate with other lighting operated by that same control; and (8) As applicable, instruments must have faceplates that replicate those in the airplane; and Level 7 FTD only; The display image of any three dimensional instrument, such as an electro-mechanical instrument, should appear to have the same three dimensional depth as the replicated instrument. The appearance of the simulated instrument, when viewed from the principle operator's angle, should replicate that of the actual airplane instrument. Any instrument reading inaccuracy due to viewing angle and parallax present in the actual airplane instrument should be duplicated in the simulated instrument display image. Viewing angle error and parallax must be minimized on shared instruments such and engine displays and standby indicators. The FTD must have equipment (e.g., instruments, panels, systems, circuit breakers, and controls) simulated sufficiently for the authorized training/checking events to be accomplished. The installed equipment must be located in a spatially correct location and may be in a flight deck or an open flight deck area. Additional equipment required for the authorized					conduct qualified training tasks.
1.b.						