

Table B1A – Minimum FTD Requirements									
Entry Number	QPS REQUIREMENTS					INFORMATION			
	General FTD Requirements					FTD Level			
						4	5	6	7
	An SOC is required and must include references to computations of aeroelastic representations and of nonlinearities due to sideslip. The FTD must have aerodynamic and ground reaction modeling for the effects of reverse thrust on directional control, if applicable.								
2.k.	An SOC is required.								X
3. Equipment Operation.									
3.a.	All relevant instrument indications involved in the simulation of the airplane must automatically respond to control movement or external disturbances to the simulated airplane; e.g., turbulence or windshear. Numerical values must be presented in the appropriate units. For Level 7 FTDs, instrument indications must also respond to effects resulting from icing.					X	X		X
3.b.1.	Navigation equipment must be installed and operate within the tolerances applicable for the airplane. Levels 6 must also include communication equipment (inter-phone and air/ground) like that in the airplane and, if appropriate to the operation being conducted, an oxygen mask microphone system. Level 5 need have only that navigation equipment necessary to fly an instrument approach.					X	X		
3.b.2.	Communications, navigation, caution, and warning equipment must be installed and operate within the tolerances applicable for the airplane. Instructor control of internal and external navigational aids. Navigation aids								X See Attachment 3 of this appendix for further information regarding long-range navigation equipment.