

Table B1A – Minimum FTD Requirements							
Entry Number	QPS REQUIREMENTS	INFORMATION					
		General FTD Requirements	FTD Level				Notes
			4	5	6	7	
	for an instructor/check airman and FAA Inspector must be available. These seats must provide adequate view of crewmember's panel(s).					replica of an aircraft seat and may be as simple as an office chair placed in an appropriate position.	
4.a.2.	In addition to the flight crewmember stations, the FTD must have at least two suitable seats for the instructor/check airman and FAA inspector. These seats must provide adequate vision to the pilot's panel and forward windows. All seats other than flight crew seats need not represent those found in the airplane, but must be adequately secured to the floor and equipped with similar positive restraint devices.					X The NSPM will consider alternatives to this standard for additional seats based on unique flight deck configurations.	
4.b.1.	The FTD must have instructor controls that permit activation of normal, abnormal, and emergency conditions as appropriate. Once activated, proper system operation must result from system management by the crew and not require input from the instructor controls.	X	X	X			
4.b.2.	The FTD must have controls that enable the instructor/evaluator to control all required system variables and insert all abnormal or emergency conditions into the simulated airplane systems as described in the sponsor's FAA-approved training program; or as described in the relevant operating manual as appropriate.					X	
4.c.	The FTD must have instructor controls for all environmental effects expected to be available at the IOS; e.g., clouds, visibility, icing, precipitation, temperature, storm cells and microbursts, turbulence, and intermediate and high altitude wind speed and direction.					X	
4.d.	The FTD must provide the instructor or evaluator the ability to present ground and air hazards.					X For example, another airplane crossing the active runway or converging airborne traffic.	