

Table B1A – Minimum FTD Requirements									
QPS REQUIREMENTS									
Entry Number	General FTD Requirements	FTD Level				Notes			
		4	5	6	7				
	An SOC is required and must explain the system geometry measurements including system linearity and field-of-view. Collimation is not required but parallax effects must be minimized (not greater than 10° for each pilot when aligned for the point midway between the left and right seat eyepoints). The visual system must be free from optical discontinuities and artifacts that create non-realistic cues.					discretion provided the minimum fields of view are retained.			
6.e.					X	Non-realistic cues might include image “swimming” and image “roll-off,” that may lead a pilot to make incorrect assessments of speed, acceleration, or situational awareness.			
6.f.	The FTD must have operational landing lights for night scenes. Where used, dusk (or twilight) scenes require operational landing lights. The FTD must have instructor controls for the following:								
6.g.	(1) Visibility in statute miles (km) and runway visual range (RVR) in ft.(m); (2) Airport selection; and (3) Airport lighting. The FTD must provide visual system compatibility with dynamic response programming.								
6.h.									
6.i.	The FTD must show that the segment of the ground visible from the FTD flight deck is the same as from the airplane flight deck (within established tolerances) when at the correct airspeed, in the landing configuration, at the appropriate height above the touchdown zone, and with appropriate visibility.					This will show the modeling accuracy of RVR, glideslope, and localizer for a given weight, configuration, and speed within			