

Table B2A - Flight Training Device (FTD) Objective Tests									
QPS REQUIREMENTS							INFORMATION		
Test		Tolerance	Flight Conditions	Test Details	FTD Level			Notes	
Entry Number	Title				5	6	7		
1.b.7.b.	Rejected Takeoff.	±5% of time or ±1.5 s.	Takeoff	Record time for at least 80% of the segment from initiation of the rejected takeoff to full stop.		X		For Level 6 FTD, this test is required only if RTO training credit is sought.	
1.b.8.	Dynamic Engine Failure After Takeoff.	±2°/s or ±20% of body angular rates.	Takeoff.	Engine failure speed must be within ±3 kt of airplane data. Engine failure may be a snap deceleration to idle. Record hands-off from 5 s before engine failure to +5 s or 30° roll angle, whichever occurs first. CCA: Test in Normal and Non-normal control state.			X	For safety considerations, airplane flight test may be performed out of ground effect at a safe altitude, but with correct airplane configuration and airspeed.	
1.c.	Climb.								
1.c.1.	Normal Climb, all engines operating.	±3 kt airspeed. ±0.5 m/s (100 ft/min) or ±5% of rate of climb.	Clean.	Flight test data are preferred; however, airplane performance manual data are an acceptable alternative. Record at nominal climb speed and mid initial climb altitude. FTD performance is to be recorded over an interval of at least 300 m (1,000 ft).	X	X	X	For Level 5 and Level 6 FTDs, this may be a snapshot test result.	
1.c.2.	One-engine-inoperative 2nd segment climb.	±3 kt airspeed. ±0.5 m/s (100 ft/min) or ±5% of rate of climb, but not less than airplane performance data requirements.	2nd segment climb.	Flight test data is preferred; however, airplane performance manual data is an acceptable alternative. Record at nominal climb speed. FTD performance is to be recorded over an interval of at least 300 m (1,000 ft). Test at WAT (weight, altitude or temperature) limiting condition.			X		