

Table B2A - Flight Training Device (FTD) Objective Tests									
QPS REQUIREMENTS									
Test		Tolerance	Flight Conditions	Test Details	FTD Level			Notes	
Entry Number	Title				5	6	7		
2.b.6.	Small Control Inputs – Yaw.	±0.15°/s body yaw rate or ±20% of peak body yaw rate applied throughout the time history.	Approach or landing.	Control inputs must be typical of minor corrections made while established on an ILS approach (approximately 0.5 to 2°/s yaw rate). Test in both directions. Show time history data from 5 s before until at least 5 s after initiation of control input. If a single test is used to demonstrate both directions, there must be a minimum of 5 s before control reversal to the opposite direction. CCA: Test in normal and non-normal control state.			X		
2.c.	Longitudinal Control Tests. Power setting is that required for level flight unless otherwise specified.								
2.c.1.a.	Power Change Dynamics.	±3 kt airspeed. ±30 m (100 ft) altitude. ±1.5° or ±20% of pitch angle.	Approach.	Power change from thrust for approach or level flight to maximum continuous or go-around power. Time history of uncontrolled free response for a time increment equal to at least 5 s before initiation of the power change to the completion of the power change + 15 s. CCA: Test in normal and non-normal control mode. May be a series of snapshot test results. Power change dynamics test as described in test 2.c.1.a. will be accepted. CCA: Test in Normal and Non-normal control mode.			X		
2.c.1.b.	Power Change Force.	±5 lb (2.2 daN) or, ±20% pitch control force.	Approach.				X		