

Table B2A - Flight Training Device (FTD) Objective Tests									
QPS REQUIREMENTS									
Test		Tolerance	Flight Conditions	Test Details	FTD Level			Notes	
Entry Number	Title				5	6	7		
2.a.9.	Directional control (rudder effectiveness) with asymmetric reverse thrust.	±5 kt airspeed. ±3° heading angle.	Landing.	With full reverse thrust on the operating engine(s), maintain heading with rudder pedal input until maximum rudder pedal input or thrust reverser minimum operation speed is reached.			X		
2.f.	Ground Effect. Test to demonstrate Ground Effect.	±1° elevator angle. ±0.5° stabilizer angle. ±5% of net thrust or equivalent. ±1° AOA. ±1.5 m (5 ft) or ±10% of height. ±3 kt airspeed. ±1° pitch angle.	Landing.	A rationale must be provided with justification of results. CCA: Test in normal or non-normal control mode, as applicable.			X		See paragraph on Ground Effect in this attachment for additional information.
2.g.	Reserved								
2.h.	Flight Maneuver and Envelope Protection Functions. <i>Note. — The requirements of 2.h are only applicable to computer-controlled airplanes. Time history results of response to control inputs during entry into each envelope protection function (i.e. with normal and degraded control states if their function is different) are required. Set thrust as required to reach the envelope protection function.</i>								
2.h.1.	Overspeed	±5 kt airspeed.	Cruise.				X		
2.h.2.	Minimum Speed.	±3 kt airspeed.	Takeoff, Cruise, and Approach or Landing.				X		
2.h.3.	Load Factor.	±0.1g normal load factor	Takeoff, Cruise.				X		
2.h.4.	Pitch Angle.	±1.5° pitch angle	Cruise, Approach.				X		
2.h.5.	Bank Angle.	±2° or ±10% bank angle	Approach.				X		
2.h.6.	Angle of Attack.	±1.5° angle of attack	Second Segment Climb.				X		