

Table B2A - Flight Training Device (FTD) Objective Tests									
QPS REQUIREMENTS						INFORMATION			
Test		Tolerance	Flight Conditions	Test Details	FTD Level			Notes	
Entry Number	Title				5	6	7		
5.c.	Special cases.	cannot exceed 2 dB. Initial evaluation: Subjective assessment of 1/3 octave bands. Recurrent evaluation: cannot exceed ± 5 dB difference on three consecutive bands when compared to initial evaluation and the average of the absolute differences between initial and recurrent evaluation results cannot exceed 2 dB.	As appropriate.					X	This applies to special steady-state cases identified as particularly significant to the pilot, important in training, or unique to a specific airplane type or model.
5.d	FTD background noise	Initial evaluation: background noise levels must fall below the sound levels described in Appendix A, Attachment 2, Paragraph 7 c (5). Recurrent evaluation: ± 3 dB per 1/3 octave band compared to initial evaluation.		Results of the background noise at initial qualification must be included in the QTC document and approved by the NSPM. The measurements are to be made with the simulation running, the sound muted and a dead cockpit.				X	The simulated sound will be evaluated to ensure that the background noise does not interfere with training. Refer to paragraph 7 of this Appendix A, Attachment 2. This test should be presented using an unweighted 1/3 octave band format from band 17 to 42 (50 Hz to 16 kHz).
5.e	Frequency response	Initial evaluation: not applicable. Recurrent evaluation: cannot exceed ± 5 dB difference on three						X	Only required if the results are to be used during continuing qualification evaluations in lieu of airplane tests. The results must be approved by