

Table B2A - Flight Training Device (FTD) Objective Tests									
QPS REQUIREMENTS					INFORMATION				
Test		Tolerance	Flight Conditions	Test Details	FTD Level			Notes	
Entry Number	Title				5	6	7		
6		consecutive bands when compared to initial evaluation and the average of the absolute differences between initial and recurrent evaluation results cannot exceed 2 dB.						the NSPM during the initial qualification. This test should be presented using an unweighted 1/3 octave band format from band 17 to 42 (50 Hz to 16 kHz).	
6.a.	SYSTEMS INTEGRATION								
	System response time								
6.a.1	Transport delay.	Instrument response: 100 ms (or less) after airplane response. Visual system response: 120 ms (or less) after airplane response.	Pitch, roll and yaw.					One separate test is required in each axis. Where EFVS systems are installed, the EFVS response should be within + or - 30 ms from visual system response, and not before motion system response. <i>Note.— The delay from the airplane EFVS electronic elements should be added to the 30 ms tolerance before comparison with visual system reference.</i>	
6.a.2	Transport delay.	300 milliseconds or less after controller movement.	Pitch, roll and yaw.		X			If transport delay is the chosen method to demonstrate relative responses, the sponsor and the NSPM will use the latency values to ensure proper FTD response when reviewing those existing tests where latency can	