

Table B2B - Alternative Data Source for FTD Level 5 Small, Single Engine (Reciprocating) Airplane			
QPS REQUIREMENT			
The performance parameters in this table must be used to program the FTD if flight test data is not used to program the FTD.			
Entry Number	Applicable Test		Authorized Performance Range
	Title and Procedure		
2.c.2.	(b) Trim for straight and level flight at 80 percent of normal cruise airspeed with necessary power. Add power to maximum setting. Do not change trim or configuration. After stabilized, record column force necessary to maintain original airspeed.		5 - 15 lbs (2.2 - 6.6 daN) of force (Pull).
	Flap/slat change force.		
	(a) Trim for straight and level flight with flaps fully retracted at a constant airspeed within the flaps-extended airspeed range. Do not adjust trim or power. Extend the flaps to 50 percent of full flap travel. After stabilized, record stick force necessary to maintain original airspeed.		5 - 15 lbs (2.2 - 6.6 daN) of force (Push).
	OR		
2.c.4.	b) Trim for straight and level flight with flaps extended to 50% of full flap travel, at a constant airspeed within the flaps-extended airspeed range. Do not adjust trim or power. Retract the flaps to zero. After stabilized, record stick force necessary to maintain original airspeed.		5 - 15 lbs (2.2 - 6.6 daN) of force (Pull).
	Gear change force.		
	(a) Trim for straight and level flight with landing gear retracted at a constant airspeed within the landing gear-extended airspeed range. Do not adjust trim or power. Extend the landing gear. After stabilized, record stick force necessary to maintain original airspeed.		2 - 12 lbs (0.88 - 5.3 daN) of force (Push).
	OR		
2.c.5.	(b) Trim for straight and level flight with landing gear extended, at a constant airspeed within the landing gear-extended airspeed range. Do not adjust trim or power. Retract the landing gear. After stabilized, record stick force necessary to maintain original airspeed.		2 - 12 lbs (0.88 - 5.3 daN) of force (Pull).
	Longitudinal trim.		Must be able to trim longitudinal stick force to "zero" in each of the following configurations: cruise; approach; and landing.
2.c.7.	Longitudinal static stability.		Must exhibit positive static stability.