

Table A2A - Full Flight Simulator (FFS) Objective Tests									
QPS REQUIREMENTS									
Test		Tolerance	Flight Conditions	Test Details	Simulator Level				Notes
Entry Number	Title				A	B	C	D	
				This test may be conducted in an on-ground condition through stimulation of the stall protection system in a manner that generates a stick pusher response that is representative of an in-flight condition.					acceptable by the NSPM. Test requirement may be met through column force validation testing in conjunction with the Stall Characteristics test (2.c.8.a.). This test is required only for FSTDs qualified to conduct full stall training tasks.
2.b.	Dynamic Control Tests. <i>Note.— Tests 2.b.1., 2.b.2 and 2.b.3 are not applicable for FSTDs where the control forces are completely generated within the airplane controller unit installed in the FSTD. Power setting may be that required for level flight unless otherwise specified. See paragraph 4 of this attachment.</i>								
2.b.1.	Pitch Control.	For underdamped systems: $T(P_0) \pm 10\%$ of P_0 or ± 0.05 s. $T(P_1) \pm 20\%$ of P_1 or ± 0.05 s. $T(P_2) \pm 30\%$ of P_2 or ± 0.05 s. $T(P_n) \pm 10\%(n+1)\%$ of P_n or ± 0.05 s. $T(A_0) \pm 10\%$ of A_{miss} where A_{miss} is the largest amplitude or $\pm 0.5\%$ of the total control travel (stop to stop).	Takoff, Cruise, and Landing.	Data must be for normal control displacements in both directions (approximately 25% to 50% of full throw or approximately 25% to 50% of maximum allowable pitch controller deflection for flight conditions limited by the maneuvering load envelope). Tolerances apply against the absolute values of each period (considered independently).			X	X	n = the sequential period of a full oscillation. Refer to paragraph 4 of this Attachment. For overdamped and critically damped systems, see Figure A2B of Appendix A for an illustration of the reference measurement.