

Table A2A – Full Flight Simulator (FFS) Objective Tests									
QPS REQUIREMENTS					INFORMATION				
Test		Tolerance	Flight Conditions	Test Details	Simulator Level				Notes
Entry Number	Title				A	B	C	D	
		±3 m (10 ft) or ±10% of height. ±2° roll angle. ±2° side-slip angle.							
2.e.5.	Autopilot landing (if applicable).	±3° heading angle. ±1.5 m (5 ft) flare height. ±0.5 s or ± 10% of TT. ±0.7 m/s (140 ft/min) rate of descent at touchdown. ±3 m (10 ft) lateral deviation during roll-out.	Landing.	If autopilot provides roll-out guidance, record lateral deviation from touchdown to a 50% decrease in main landing gear touchdown speed. Time of autopilot flare mode engage and main gear touchdown must be noted.	X	X	X	X	See Appendix F of this part for definition of T _r .
2.e.6.	All-engine autopilot go-around.	±3 kt airspeed. ±1.5° pitch angle. ±1.5° AOA.	As per airplane performance data.	Normal all-engine autopilot go-around must be demonstrated (if applicable) at medium weight.	X	X	X	X	
2.e.7.	One engine inoperative go-around.	±3 kt airspeed. ±1.5° pitch angle. ±1.5° AOA. ±2° roll angle. ±2° side-slip angle.	As per airplane performance data.	Engine inoperative go-around required near maximum certificated landing weight with critical engine inoperative. Provide one test with autopilot (if applicable) and one without autopilot. CCA: Non-autopilot test to be conducted in non-normal mode.	X	X	X	X	