

TABLE 1b—CHANNELS—Continued

Channel pairing				DME parameters					
DME No.	VHF freq. MHz	MLS angle freq. MHz	MLS Ch. No.	Interrogation			Reply		
				Freq. MHz	Pulse codes				
					DME/N μs	DME/P Mode		Freq. MHz	Pulse codes μs
IA μs	FA μs								
73X	112.60			1097	12		1160	12	
**73Y	112.65			1097	36		1034	30	
74X	112.70			1098	12		1161	12	
**74Y	112.75			1098	36		1035	30	
75X	112.80			1099	12		1162	12	
**75Y	112.85			1099	36		1036	30	
76X	112.90			1100	12		1163	12	
**76Y	112.95			1100	36		1037	30	
77X	113.00			1101	12		1164	12	
**77Y	113.05			1101	36		1038	30	
78X	113.10			1102	12		1165	12	
**78Y	113.15			1102	36		1039	30	
79X	113.20			1103	12		1166	12	
**79Y	113.25			1103	36		1040	30	
80X	113.30			1104	12		1167	12	
80Y	113.35	5067.0	620	1104	36	36 42	1041	30	
80Z		5067.3	621	1104		21 27	1041	15	
81X	113.40			1105	12		1168	12	
81Y	113.45	5067.6	622	1105	36	36 42	1042	30	
81Z		5067.9	623	1005		21 27	1042	15	
82X	113.50			1106	12		1169	12	
82Y	113.55	5068.2	624	1106	36	36 42	1043	30	
82Z		5068.5	625	1106		21 27	1043	15	
83X	113.60			1107	12		1170	12	
83Y	113.65	5068.8	626	1107	36	36 42	1044	30	
83Z		5069.1	627	1107		21 27	1044	15	
84X	113.70			1108	12		1171	12	
84Y	113.75	5069.4	628	1108	36	36 42	1045	30	
84Z		6069.7	629	1108		21 27	1045	15	
85X	113.80			1109	12		1172	12	
85Y	113.85	5070.0	630	1109	36	36 42	1046	30	
85Z		5070.3	631	1109		21 27	1046	15	
86X	113.90			1110	12		1173	12	
86Y	113.95	5070.6	632	1110	36	36 42	1047	30	
86Z		5070.9	633	1110		21 27	1047	15	
87X	114.00			1111	12		1174	12	
87Y	114.05	5071.2	634	1111	36	36 42	1048	30	
87Z		5071.5	635	1111		21 27	1048	15	
88X	114.10			1112	12		1175	12	
88Y	114.15	5071.8	636	1112	36	36 42	1049	30	
88Z		5072.1	637	1112		21 27	1049	15	
89X	114.20			1113	12		1176	12	
89Y	114.25	5072.4	638	1113	36	36 42	1050	30	
89Z		5072.7	639	1113		21 27	1050	15	
90X	114.30			1114	12		1177	12	
90Y	114.35	5073.0	640	1114	36	36 42	1051	30	
90Z		5073.3	641	1114		21 27	1051	15	
91X	114.40			1115	12		1178	12	
91Y	114.45	5073.6	642	1115	36	36 42	1052	30	
91Z		5073.9	643	1115		21 27	1052	15	
92X	114.50			1116	12		1179	12	
92Y	114.55	5074.2	644	1116	36	36 42	1053	30	
92Z		5074.5	645	1116		21 27	1053	15	
93X	114.60			1117	12		1180	12	
93Y	114.65	5074.8	646	1117	36	36 42	1054	30	
93Z		5075.1	647	1117		21 27	1054	15	
94X	114.70			1118	12		1181	12	
94Y	114.75	5075.4	648	1118	36	36 42	1055	30	
94Z		5075.7	649	1118		21 27	1055	15	
95X	114.80			1119	12		1182	12	
95Y	114.85	5076.0	650	1119	36	36 42	1056	30	
95Z		5076.3	651	1119		21 27	1056	15	
96X	114.90			1120	12		1183	12	
96Y	114.95	5076.6	652	1120	36	36 42	1057	30	
96Z		5076.9	653	1120		21 27	1057	15	