Pipeline and Haz. Matls. Safety Admin., DOT



(b) In addition to complying with §172.519 of this subpart, the background color on the EXPLOSIVES 1.4 placard must be orange. The "*" shall be replaced, when required, with the appropriate compatibility group letter. The division numeral, 1.4, must measure at least 64 mm (2.5 inches) in height. The text, numerals and inner border must be black.

 $[{\rm Amdt.}\ 172{-}123,\ 55\ {\rm FR}\ 52602,\ {\rm Dec.}\ 21,\ 1990,\ {\rm as}$ amended at 56 ${\rm FR}\ 66261,\ {\rm Dec.}\ 20,\ 1991]$

§172.524 EXPLOSIVES 1.5 placard.

(a) Except for size and color, the EX-PLOSIVES 1.5 placard must be as follows:



(b) In addition to complying with the §172.519 of this subpart, the background color on EXPLOSIVES 1.5 placard

must be orange. The "*" shall be replaced, when required, with the appropriate compatibility group letter. The division numeral, 1.5, must measure at least 64 mm (2.5 inches) in height. The text, numerals and inner border must be black.

 $[{\rm Amdt.}\ 172{-}123,\ 55\ {\rm FR}\ 52602,\ {\rm Dec.}\ 21,\ 1990,\ as$ amended at 56 ${\rm FR}\ 66261,\ {\rm Dec.}\ 20,\ 1991]$

§172.525 EXPLOSIVES 1.6 placard.

(a) Except for size and color the EX-PLOSIVES 1.6 placard must be as follows:



(b) In addition to complying with §172.519 of this subpart, the background color on the EXPLOSIVES 1.6 placard must be orange. The "*" shall be replaced, when required, with the appropriate compatibility group letter. The division numeral, 1.6, must measure at least 64 mm (2.5 inches) in height. The text, numerals and inner border must be black.

[Amdt. 172-123, 55 FR 52603, Dec. 21, 1990, as amended at 56 FR 66261, Dec. 20, 1991; Amdt. 172-130, 58 FR 51531, Oct. 1, 1993]

§172.526 [Reserved]

§172.527 Background requirements for certain placards.

(a) Except for size and color, the square background required by §172.510(a) for certain placards on rail cars, and §172.507 for placards on motor vehicles containing a package of highway route controlled quantity radioactive materials, must be as follows: